

# Allura Neo LA - 2 TL - #1456



30W



2811lm





4000K















Photometric Data	
Light source	LED - Array
Power (W)	30W
Delivered lumens	2811lm
Source lumens	3960lm
Colour temperature (K)	4000K
Luminaire efficacy	93.7lm/W
Beam angle	38°
Cutoff angle	37°

Light output ratio	70%	
Color rendering index (Ra)	>95	
Color rendering index (R9)	>85	
Binning MacAdam	<2 SDCM	
LED life	L90 B10 Tj75°C	
UGR	<16	
Operating temperature	-20°C to +50°C	
Light distribution	Direct - Symmetric	








Technical Data	
Mounting detail	Ceiling - Recessed 1-25mm
Fixing detail	Dual tension spring
Orientation	Adjustable
IP rating	IP44
Glow wire test	850°
Trim material	Diecast alm.
Heatsink material	Diecast alm.

Product weight	411gms
Safety class	III
Insulation class	
LED current (mA)	750mA
Voltage	220V-240V
Forward voltage	36V
Driver	Remote




#### Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity
Graph



## **Finish Options**

#### Trim Finish

- Matt White
- Matt Black
- Custom RAL Color

## Interior Finish

- Matt White
- Matt Black
- Specular
- Pearl Black
- Matt Silver
- Matt Gold

## **Filter Options**



Honeycomb Filter

Above filters can be added to the fixture and need to be ordered as a separate accessory

## **Dimming Options**



Constant Current Driver 30w 750mA 220-240V Non Dimmable



Constant Current Driver 30w 750mA 220-240V Dali Dimmable



Constant Current Driver 30w 750mA 220-240V Triac Dimmable



Constant Current Driver 30w 750mA 220-240V Dali Tunable



Constant Current Driver 30w 750mA 220-240V Analog 0-10V / 1-10V Dimmable



Constant Current Driver 30w 750mA 220-240V RF Tunable (operated with RF remote)

L'azure constantly strives to improve our products using the latest technological advancements in the industry.

Due to which the data mentioned in the data sheet is subject to change without prior notice.