

Aurele Ring Pendant M - #1403



36W





3120lm



3000K




Diffused



Photometric Data

Light source	LED - Mid Power	Light output ratio	66%
Power (W)	36W	Color rendering index (Ra)	>92
Delivered lumens	3120lm	Color rendering index (R9)	>50
Source lumens	4716lm	Binning MacAdam	<3 SDCM
Colour temperature (K)	3000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	86.66lm/W	UGR	<19
Beam angle	Diffused	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Diffused




Technical Data


Mounting detail	Ceiling - Pendant	Product weight	576gms
Fixing detail	Hanging Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	600mA
Glow wire test	850°	Voltage	AC230V
Trim material	Aluminium	Forward voltage	DC60V
Heatsink material	Aluminium	Driver	CC - Remote

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Trim Finish

- ☐ Matt White
- ☐ Matt Black
- ☐ Custom RAL Color

Interior Finish

NA

Dimming Options



Constant Current Driver
36w 600mA 220-240V
Non Dimmable



Constant Current Driver
36w 600mA 220-240V
Triac Dimmable



Constant Current Driver
36w 600mA 220-240V
Analog 0-10V / 1-10V Dimmable



Constant Current Driver
36w 600mA 220-240V
Dali Dimmable

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Aurele Ring Pendant M - #1403



36W




3215lm



4000K




Diffused



Photometric Data

Light source	LED - Mid Power	Light output ratio	64%
Power (W)	36W	Color rendering index (Ra)	>92
Delivered lumens	3215lm	Color rendering index (R9)	>50
Source lumens	5004lm	Binning MacAdam	<3 SDCM
Colour temperature (K)	4000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	89.30lm/W	UGR	<19
Beam angle	Diffused	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Diffused




Technical Data


Mounting detail	Ceiling - Pendant	Product weight	576gms
Fixing detail	Hanging Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	600mA
Glow wire test	850°	Voltage	AC230V
Trim material	Aluminium	Forward voltage	DC60V
Heatsink material	Aluminium	Driver	CC - Remote

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Trim Finish

- ☐ Matt White
- ☐ Matt Black
- ☒ Custom RAL Color

Interior Finish

NA

Dimming Options



Constant Current Driver
36w 600mA 220-240V
Non Dimmable



Constant Current Driver
36w 600mA 220-240V
Triac Dimmable



Constant Current Driver
36w 600mA 220-240V
Analog 0-10V / 1-10V Dimmable



Constant Current Driver
36w 600mA 220-240V
Dali Dimmable

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.