

Kosmos - Flexi Curtain - #2214



15W/M




1441lm/m



3000K




30°



Photometric Data

Light source	LED - High Power	Light output ratio	69%
Power (W)	15W/M	Color rendering index (Ra)	> 92
Delivered lumens	1441lm/m	Color rendering index (R9)	> 50
Source lumens	2062lm/m	Binning MacAdam	< 3 SDCM
Colour temperature (K)	3000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	96.06lm/W	UGR	< 19
Beam angle	30°	Operating temperature	-20°C to + 50°C
Cutoff angle	NA	Light distribution	Grazer




Technical Data


Mounting detail	Surface Mounted	Glow wire test	850°
Fixing detail	Mounting Clamp	Safety class	III
Orientation	Top & Side Bendable	Insulation class	III
IP rating	IP67	Driver Input Voltage	AC230V
Trim material	NA	Fixture voltage	DC24V
Heatsink material	Silicone	Driver	CV - Remote

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Custom RAL Color


Length

5000MM

Accessories Options



Top Bend
Radius 300mm
Radius 300mm



Front
Cable Entry



Bottom
Cable Entry



Mounting
Chain



Mounting
Clamp



Mounting
Profile

Dimming Options



Constant Voltage Driver
75w DC24V
Non Dimmable



Constant Voltage Driver
75w DC24V
Triac Dimmable



Constant Voltage Driver
75w DC24V
Analog 0-10V / 1-10V Dimmable



Constant Voltage Driver
75w DC24V
Dali Dimmable

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.