

# Marcopia Round 8 - #3021



72W





3357lm



Blue





60°



## Photometric Data

|                        |                  |                       |                    |
|------------------------|------------------|-----------------------|--------------------|
| Light source           | LED - High Power | Beam angle            | 60°                |
| Power (W)              | 72W              | Light output ratio    | 81%                |
| Delivered lumens       | 3357lm           | LED life              | L90 B10 Tj75°C     |
| Source lumens          | 4104lm           | UGR                   | <19                |
| Colour temperature (K) | Blue             | Operating temperature | -20°C to +50°C     |
| Luminaire efficacy     | 46.62lm/W        | Light distribution    | Direct - Symmetric |



## Technical Data

|                 |                                                   |                   |                |
|-----------------|---------------------------------------------------|-------------------|----------------|
| Mounting detail | Surface Uplighter                                 | Heatsink material | Diecast alm.   |
| Fixing detail   | Cowl / Tree Strap / Pole Bracket / Mounting Plate | Product weight    | 4098gms        |
| Orientation     | Adjustable                                        | Safety class      | III            |
| IP rating       | IP65                                              | Insulation class  | III            |
| IK rating       | IK05                                              | Voltage           | DC24V          |
| Glow wire test  | 850°                                              | Driver            | Remote - DC24V |

## Finish Options

### Body Finish

- Matt Grey
- Custom RAL Color

## Filter Options



Honeycomb Filter

Above filters can be added to the fixture and need to be ordered as a separate accessory

## Accessories Options



Cowl



Tree Strap



Pole Bracket

Above accessories can be added to the fixture and need to be ordered as a separate accessory

## Dimming Options



In-built DMX Decoder

The DMX Decoder requires a 24V CV Driver