

# Marcopia Square 6 - #3009



72W





3944lm



Red




45°



## Photometric Data

|                        |                  |                       |                    |
|------------------------|------------------|-----------------------|--------------------|
| Light source           | LED - High Power | Beam angle            | 45°                |
| Power (W)              | 72W              | Light output ratio    | 81%                |
| Delivered lumens       | 3944lm           | LED life              | L90 B10 Tj75°C     |
| Source lumens          | 4896lm           | UGR                   | <19                |
| Colour temperature (K) | Red              | Operating temperature | -20°C to +50°C     |
| Luminaire efficacy     | 54.77lm/W        | Light distribution    | Direct - Symmetric |



## Technical Data

|                 |                            |                   |                |
|-----------------|----------------------------|-------------------|----------------|
| Mounting detail | Surface Uplighter          | Heatsink material | Diecast alm.   |
| Fixing detail   | Cowl /<br>Mounting Bracket | Product weight    | 3984gms        |
| Orientation     | Adjustable                 | Safety class      | III            |
| IP rating       | IP65                       | Insulation class  | III            |
| IK rating       | IK05                       | Voltage           | DC24V          |
| Glow wire test  | 850°                       | Driver            | Remote - DC24V |

## Finish Options

### Body Finish

- Matt Grey
- Custom RAL Color

## Filter Options



Honeycomb Filter

Above filters can be added to the fixture and need to be ordered as a separate accessory

## Accessories Options



Cowl

Above accessories can be added to the fixture and need to be ordered as a separate accessory

## Dimming Options



In-built DMX Decoder

The DMX Decoder requires a 24V CV Driver