


Numinous - Profile L




Recessed L
#2129

- Choose Profile - Numinous Recessed L #2129
- Choose the desired Jointer 'I' or 'L' depending on the requirement. Note :- The maximum available straight length is 3000mm
- Choose the desired modules i.e Brick - 190mm, Wash - 190mm, Diffused - 200mm or Blank. The overall length of the Numinous fixture is dependent on the no of modules selected. Note :- All of this modules can be used besides one another. Blank Module can be used where no desired lighting is required to achieved seamless installation.

Jointer



'I' Jointer



'L' Jointer




Pendant L
#2130

- Choose Profile - Numinous Pendant L #2130
- Choose the desired Jointer 'I' or 'L' depending on the requirement. Note :- The maximum available straight length is 3000mm
- Choose the desired modules i.e Brick - 190mm, Wash - 190mm, Diffused - 200mm or Blank. The overall length of the Numinous fixture is dependent on the no of modules selected. Note :- All of this modules can be used besides one another. Blank Module can be used where no desired lighting is required to achieved seamless installation.

Jointer



'I' Jointer



'L' Jointer

Connection Module



L - Module
300x43x40 - 2



+ - Module
300x43x40 - 4



X - Module
300x43x40 - 4



L - Blank

L - Wash 190

L - Diffused 200

L - Brick 190

L - Blank

Module L - Brick 190 - #2131



12W





1107lm



2700K





24°



Photometric Data

Light source	LED - High Power	Light output ratio	69%
Power (W)	12W	Color rendering index (Ra)	> 92
Delivered lumens	1107lm	Color rendering index (R9)	> 50
Source lumens	1590lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	2700K	LED life	L90 B10 Tj75°C
Luminaire efficacy	92.31lm/W	UGR	< 16
Beam angle	24°	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Recessed / Pendant	Product weight	229gms Per 190MM
Fixing detail	Spring / Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V / DC24V
Trim material	Aluminium	Forward voltage	DC36V
Heatsink material	Aluminium Extrusion	Driver	Remote - Recessed In-built - Pendant

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
Remote / In-built Driver



Triac Dimmable
Remote / In-built Driver



Analog 0-10V / 1-10V Dimmable
Remote / In-built Driver



Dali Dimmable
Remote / In-built Driver

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.