

Pendant L - Wash - #2143



36W




2847lm



2700K




Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	59%
Power (W)	36W	Color rendering index (Ra)	> 92
Delivered lumens	2847lm	Color rendering index (R9)	> 50
Source lumens	4770lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	2700K	LED life	L90 B10 Tj75°C
Luminaire efficacy	79.08lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric



Technical Data


Mounting detail	Pendant	Product weight	2516gms Per 1144MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 12W/190mm for Numinous L, the maximum capacity that the profile in which the modules are placed is 30W/m for Numinous L profile.
- The standard lengths for the Numinous Pendant L fixtures is 1144mm including the endcaps. Each fixture of length 1144mm contains 6 pieces of modules which are placed side by side in the Numinous Pendant L Profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant L - Wash - #2143



36W




2880lm



3000K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	58%
Power (W)	36W	Color rendering index (Ra)	> 92
Delivered lumens	2880lm	Color rendering index (R9)	> 50
Source lumens	4950lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	3000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	80lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Pendant	Product weight	2516gms Per 1144MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 12W/190mm for Numinous L, the maximum capacity that the profile in which the modules are placed is 30W/m for Numinous L profile.
- The standard lengths for the Numinous Pendant L fixtures is 1144mm including the endcaps. Each fixture of length 1144mm contains 6 pieces of modules which are placed side by side in the Numinous Pendant L Profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant L - Wash - #2143



36W




2998lm



4000K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	58%
Power (W)	36W	Color rendering index (Ra)	> 92
Delivered lumens	2998lm	Color rendering index (R9)	> 50
Source lumens	5130lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	4000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	83.27lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Pendant	Product weight	2516gms Per 1144MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 12W/190mm for Numinous L, the maximum capacity that the profile in which the modules are placed is 30W/m for Numinous L profile.
- The standard lengths for the Numinous Pendant L fixtures is 1144mm including the endcaps. Each fixture of length 1144mm contains 6 pieces of modules which are placed side by side in the Numinous Pendant L Profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant L - Wash - #2143



72W





5694lm



2700K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	59%
Power (W)	72W	Color rendering index (Ra)	> 92
Delivered lumens	5694lm	Color rendering index (R9)	> 50
Source lumens	9540lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	2700K	LED life	L90 B10 Tj75°C
Luminaire efficacy	79.08lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric



Technical Data


Mounting detail	Pendant	Product weight	5441gms Per 2474MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 12W/190mm for Numinous L, the maximum capacity that the profile in which the modules are placed is 30W/m for Numinous L profile.
- The standard lengths for the Numinous Pendant L fixtures is 2474mm including the endcaps. Each fixture of length 2474mm contains 13 pieces of modules which are placed side by side in the Numinous Pendant L Profile. Kindly note - there are no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant L - Wash - #2143



72W





5760lm



3000K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	58%
Power (W)	72W	Color rendering index (Ra)	> 92
Delivered lumens	5760lm	Color rendering index (R9)	> 50
Source lumens	9900lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	3000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	80lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Pendant	Product weight	5441gms Per 2474MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 12W/190mm for Numinous L, the maximum capacity that the profile in which the modules are placed is 30W/m for Numinous L profile.
- The standard lengths for the Numinous Pendant L fixtures is 2474mm including the endcaps. Each fixture of length 2474mm contains 13 pieces of modules which are placed side by side in the Numinous Pendant L Profile. Kindly note - there are no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant L - Wash - #2143



72W





5996lm



4000K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	58%
Power (W)	72W	Color rendering index (Ra)	> 92
Delivered lumens	5996lm	Color rendering index (R9)	> 50
Source lumens	10260lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	4000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	83.27lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Pendant	Product weight	5441gms Per 2474MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 12W/190mm for Numinous L, the maximum capacity that the profile in which the modules are placed is 30W/m for Numinous L profile.
- The standard lengths for the Numinous Pendant L fixtures is 2474mm including the endcaps. Each fixture of length 2474mm contains 13 pieces of modules which are placed side by side in the Numinous Pendant L Profile. Kindly note - there are no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.