

Pendant M - Wash - #2139



24W




1884lm



2700K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	59%
Power (W)	24W	Color rendering index (Ra)	> 92
Delivered lumens	1884lm	Color rendering index (R9)	> 50
Source lumens	3180lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	2700K	LED life	L90 B10 Tj75°C
Luminaire efficacy	78.5lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric



Technical Data


Mounting detail	Pendant	Product weight	1985gms Per 1196MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 10W/133mm for Numinous M, the maximum capacity that the profile in which the modules are placed is 20W/m for Numinous M profile.
- The standard lengths for the Numinous Pendant M fixtures is 1196mm including the endcaps. Each fixture of length 1196mm contains 9 pieces of modules which are placed side by side in the Numinous Pendant M profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant M - Wash - #2139



24W




1932lm



3000K




Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	58%
Power (W)	24W	Color rendering index (Ra)	> 92
Delivered lumens	1932lm	Color rendering index (R9)	> 50
Source lumens	3300lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	3000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	80.5lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Pendant	Product weight	1985gms Per 1196MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 10W/133mm for Numinous M, the maximum capacity that the profile in which the modules are placed is 20W/m for Numinous M profile.
- The standard lengths for the Numinous Pendant M fixtures is 1196mm including the endcaps. Each fixture of length 1196mm contains 9 pieces of modules which are placed side by side in the Numinous Pendant M profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant M - Wash - #2139



24W




1992lm



4000K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	58%
Power (W)	24W	Color rendering index (Ra)	> 92
Delivered lumens	1992lm	Color rendering index (R9)	> 50
Source lumens	3420lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	4000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	83lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Pendant	Product weight	1985gms Per 1196MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 10W/133mm for Numinous M, the maximum capacity that the profile in which the modules are placed is 20W/m for Numinous M profile.
- The standard lengths for the Numinous Pendant M fixtures is 1196mm including the endcaps. Each fixture of length 1196mm contains 9 pieces of modules which are placed side by side in the Numinous Pendant M profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant M - Wash - #2139



48W





3768lm



2700K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	59%
Power (W)	48W	Color rendering index (Ra)	> 92
Delivered lumens	3768lm	Color rendering index (R9)	> 50
Source lumens	6360lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	2700K	LED life	L90 B10 Tj75°C
Luminaire efficacy	78.5lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric



Technical Data


Mounting detail	Pendant	Product weight	3965gms Per 2389MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☐ Matt Black
- ☒ Custom RAL Color

Reflector Finish

- ☐ Specular
- ☒ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 10W/133mm for Numinous M, the maximum capacity that the profile in which the modules are placed is 20W/m for Numinous M profile.
- The standard lengths for the Numinous Pendant M fixtures is 2389mm including the endcaps. Each fixture of length 2389mm contains 18 pieces of modules which are placed side by side in the Numinous Pendant M Profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant M - Wash - #2139



48W





3864lm



3000K





Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	58%
Power (W)	48W	Color rendering index (Ra)	> 92
Delivered lumens	3864lm	Color rendering index (R9)	> 50
Source lumens	6600lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	3000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	80.5lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric



Technical Data


Mounting detail	Pendant	Product weight	3965gms Per 2389MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 10W/133mm for Numinous M, the maximum capacity that the profile in which the modules are placed is 20W/m for Numinous M profile.
- The standard lengths for the Numinous Pendant M fixtures is 2389mm including the endcaps. Each fixture of length 2389mm contains 18 pieces of modules which are placed side by side in the Numinous Pendant M Profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.

Pendant M - Wash - #2139



48W






3984lm



4000K




Wallwash



Photometric Data

Light source	LED - High Power	Light output ratio	58%
Power (W)	48W	Color rendering index (Ra)	> 92
Delivered lumens	3984lm	Color rendering index (R9)	> 50
Source lumens	6840lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	4000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	83lm/W	UGR	< 16
Beam angle	Wallwash	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Pendant	Product weight	3965gms Per 2389MM
Fixing detail	Suspension Wire	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☐ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☐ Specular
- ☐ Pearl Black

Dimming Options



Non Dimmable
In-built Driver



Triac Dimmable
In-built Driver



Analog 0-10V / 1-10V Dimmable
In-built Driver



Dali Dimmable
In-built Driver

Note :-

- Although the maximum capacity of the Modules is 10W/133mm for Numinous M, the maximum capacity that the profile in which the modules are placed is 20W/m for Numinous M profile.
- The standard lengths for the Numinous Pendant M fixtures is 2389mm including the endcaps. Each fixture of length 2389mm contains 18 pieces of modules which are placed side by side in the Numinous Pendant M Profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.