

Pullout - Frame S T - #1242



2x7W




2x627lm




3000K











Photometric Data
Light source LED - Array
Power (W) 2x7W

Delivered lumens 2x627lm


Source lumens 2x847lm

Colour temperature (K) 3000K

Luminaire efficacy 89.58lm/W

Beam angle 15°

Light output ratio	74%
Color rendering index (Ra)	>95
Color rendering index (R9)	>85
Binning MacAdam	<2 SDCM
LED life	L90 B10 Tj75°C
UGR	<19
Operating temperature	-20°C to +50°C
Light distribution	Direct - Symmetric



Cutoff angle



NA


Technical Data		
Mounting detail	Ceiling - Recessed 1-25mm	
Fixing detail	Dual tension spring	
Orientation	Adjustable	
IP rating	IP20	
Glow wire test	850°	
Trim material	Diecast alm.	
Heatsink material	Diecast alm.	

Product weight	294gms
Safety class	III
Insulation class	III
LED current (mA)	190mA
Voltage	AC230V
Forward voltage	DC36V
Driver	CC - Remote




Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity
Graph



Finish Options

Trim Finish

- Matt White
- Matt Black
- Custom RAL Color

Interior Finish

- Matt White
- Matt Black
- Matt Silver
- Matt Gold

Filter Options



Honeycomb Filter



Softening Lens

Above filters can be added to the fixture and need to be ordered as a separate accessory

Dimming Options



Constant Current Driver 7w 190mA 220-240V Non Dimmable



Constant Current Driver 7w 190mA 220-240V Dali Dimmable



Constant Current Driver 7w 190mA 220-240V Triac Dimmable



Constant Current Driver 7w 190mA 220-240V Dali Tunable



Constant Current Driver 7w 190mA 220-240V Analog 0-10V / 1-10V Dimmable



Constant Current Driver 7w 190mA 220-240V RF Tunable (operated with RF remote)

L'azure constantly strives to improve our products using the latest technological advancements in the industry.

Due to which the data mentioned in the data sheet is subject to change without prior notice.