

Trinsic Ace S - #1357



18W




1750lm



4000K











Photometric Data			
Light source	LED - Array	Light output ratio	70%
Power (W)	18W	Color rendering index (Ra)	>95
Delivered lumens	1750lm	Color rendering index (R9)	>85
Source lumens	2447lm	Binning MacAdam	<2 SDCM
Colour temperature (K)	4000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	97.2lm/W	UGR	<19
Beam angle	45°	Operating temperature	-20°C to +50°C
Cutoff angle	16°	Light distribution	Direct - Symmetric








Technical Data	
Mounting detail	Track Mounted
Fixing detail	Track Channel
Orientation	Adjustable
IP rating	IP44
Glow wire test	850°
Trim material	NA
Heatsink material	Diecast alm.

Product weight	329gms
Safety class	III
Insulation class	III
LED current (mA)	250mA
Voltage	AC230V
Forward voltage	DC36V
Driver	Remote




Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity
Graph



Finish Options

Body Finish

- Matt White
- Matt Black
- Custom RAL Color

Interior Finish

- Matt White
- Matt Black
 - Matt Silver
 - Matt Gold

Filter Options



Honeycomb Filter



Above filters can be added to the fixture and need to be ordered as a separate accessory

Dimming Options



Constant Current Driver 18w 250mA 220-240V Non Dimmable



Constant Current Driver 18w 250mA 220-240V Dali Dimmable



Constant Current Driver 18w 250mA 220-240V Triac Dimmable



Constant Current Driver 18w 250mA 220-240V Analog 0-10V / 1-10V Dimmable

L'azure constantly strives to improve our products using the latest technological advancements in the industry.

Due to which the data mentioned in the data sheet is subject to change without prior notice.