

Brick 1x2 - #1254



4W



379lm





2700K



24°









€ 66x37

Photometric Data	
Light source	LED - High Power
Power (W)	4W
Delivered lumens	379lm
Source lumens	530lm
Colour temperature (K)	2700K
Luminaire efficacy	94.81lm/W
Beam angle	24°
Cutoff angle	23°

Light output ratio	71%
Color rendering index (Ra)	>92
Color rendering index (R9)	>50
Binning MacAdam	<3 SDCM
LED life	L90 B10 Tj75°C
UGR	<19
Operating temperature	-20°C to +50°C
Light distribution	Direct - Symmetric








Technical Data	
Mounting detail	Ceiling - Recessed 1-25mm
Fixing detail	Dual tension spring
Orientation	Fixed
IP rating	IP20
Glow wire test	850°
Trim material	Diecast alm.
Heatsink material	Diecast alm.

Product weight	124gms
Safety class	III
Insulation class	III
LED current (mA)	500mA
Voltage	AC230V
Forward voltage	DC6V
Driver	CC - Remote




Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity
Graph



Finish Options

Trim Finish

- Matt White
- Matt Black
- Custom RAL Color

Reflector Finish

- Specular
- Pearl Black

Dimming Options



Constant Current Driver 4w 500mA 220-240V Non Dimmable



Constant Current Driver 4w 500mA 220-240V Dali Dimmable



Constant Current Driver 4w 500mA 220-240V Triac Dimmable



Constant Current Driver 4w 500mA 220-240V Dali Tunable



Constant Current Driver 4w 500mA 220-240V Analog 0-10V / 1-10V Dimmable



Constant Current Driver 4w 500mA 220-240V RF Tunable (operated with RF remote)

L'azure constantly strives to improve our products using the latest technological advancements in the industry.

Due to which the data mentioned in the data sheet is subject to change without prior notice.