

Brick - Trim 1x3 - #1260



6W






595lm



2700K



60°





84x37

Photometric Data

Light source	LED - High Power
Power (W)	6W
Delivered lumens	595lm
Source lumens	795lm
Colour temperature (K)	2700K
Luminaire efficacy	99.26lm/W
Beam angle	60°
Cutoff angle	23°

Light output ratio	74%
Color rendering index (Ra)	>92
Color rendering index (R9)	>50
Binning MacAdam	<3 SDCM
LED life	L90 B10 Tj75°C
UGR	<19
Operating temperature	-20°C to +50°C
Light distribution	Direct - Symmetric



Technical Data

Mounting detail	Ceiling - Recessed 1-25mm
Fixing detail	Dual tension spring
Orientation	Fixed
IP rating	IP20
Glow wire test	850°
Trim material	Diecast alm.
Heatsink material	Diecast alm.

Product weight	186gms
Safety class	III
Insulation class	III
LED current (mA)	500mA
Voltage	AC230V
Forward voltage	DC9V
Driver	CC - Remote

Photometric Graphs

Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Trim Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Constant Current Driver
6w 500mA 220-240V
Non Dimmable



Constant Current Driver
6w 500mA 220-240V
Triac Dimmable



Constant Current Driver
6w 500mA 220-240V
Analog 0-10V / 1-10V Dimmable



Constant Current Driver
6w 500mA 220-240V
Dali Dimmable



Constant Current Driver
6w 500mA 220-240V
Dali Tunable



Constant Current Driver
6w 500mA 220-240V
RF Tunable (operated with RF remote)

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.