

Brick - Trimless 1x3 - #1261



6W







580lm



4000K




15°



Photometric Data

Light source	LED - High Power	Light output ratio	67%
Power (W)	6W	Color rendering index (Ra)	>92
Delivered lumens	580lm	Color rendering index (R9)	>50
Source lumens	855lm	Binning MacAdam	<3 SDCM
Colour temperature (K)	4000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	96.66lm/W	UGR	<19
Beam angle	15°	Operating temperature	-20°C to +50°C
Cutoff angle	23°	Light distribution	Direct - Symmetric



Technical Data

Mounting detail	Ceiling - Recessed 1-25mm	Product weight	249gms
Fixing detail	Mounting with Screw	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	500mA
Glow wire test	850°	Voltage	AC230V
Trim material	NA	Forward voltage	DC9V
Heatsink material	Diecast alm.	Driver	CC - Remote

Photometric Graphs

Hue Bin vs Rf Graph



Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Constant Current Driver
6w 500mA 220-240V
Non Dimmable



Constant Current Driver
6w 500mA 220-240V
Triac Dimmable



Constant Current Driver
6w 500mA 220-240V
Analog 0-10V / 1-10V Dimmable



Constant Current Driver
6w 500mA 220-240V
Dali Dimmable



Constant Current Driver
6w 500mA 220-240V
Dali Tunable



Constant Current Driver
6w 500mA 220-240V
RF Tunable (operated with RF remote)

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.