

# Allura Neo SF - 2 T - #1423



10W



893lm





3000K















Photometric Data	
Light source	LED - Array
Power (W)	10W
Delivered lumens	893lm
Source lumens	1210lm
Colour temperature (K)	3000K
Luminaire efficacy	89.31lm/W
Beam angle	24°
Cutoff angle	39°

	Light output ratio	73%
	Color rendering index (Ra)	>95
	Color rendering index (R9)	>85
	Binning MacAdam	<2 SDCM
	LED life	L90 B10 Tj75°C
	UGR	<16
	Operating temperature	-20°C to +50°C
	Light distribution	Direct - Symmetric








Technical Data		
Mounting detail	Ceiling - Recessed 1-25mm	
Fixing detail	Dual tension spring	
Orientation	Fixed	
IP rating	IP44	
Glow wire test	850°	
Trim material	Diecast alm.	
Heatsink material	Diecast alm.	

Product weight	122gms
Safety class	m
Insulation class	III
LED current (mA)	250mA
Voltage	220V-240V
Forward voltage	36V
Driver	Remote



#### Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



## **Finish Options**

#### Trim Finish

- Matt White
- Matt Black
- Custom RAL Color

## Interior Finish

- ) Matt White
- Matt Black
- Specular
- Pearl Black
- Matt Silver
- Matt Gold

## Filter Options



Honeycomb Filter

Above filters can be added to the fixture and need to be ordered as a separate accessory

## **Dimming Options**



Constant Current Driver 10w 250mA 220-240V Non Dimmable



Constant Current Driver 10w 250mA 220-240V Dali Dimmable



Constant Current Driver 10w 250mA 220-240V Triac Dimmable



Constant Current Driver 10w 250mA 220-240V Dali Tunable



Constant Current Driver 10w 250mA 220-240V Analog 0-10V / 1-10V Dimmable



Constant Current Driver 10w 250mA 220-240V RF Tunable (operated with RF remote)

L'azure constantly strives to improve our products using the latest technological advancements in the industry.

Due to which the data mentioned in the data sheet is subject to change without prior notice.