

Joule Discreet Magnetic - Track



#2248

- Shows an isometric render & 2D view of Joule Discreet Magnetic

 Track. Joule Discreet can only be mounted at the surface but
 because the product is 7 mm slim it blends with the ceiling.
- Available accessories that are needed for the installation of Joule Discreet Magnetic-Track are mentioned below. Accessories needs to be ordered separately.
- With the accessory "Wall Hanging Swinging Head" Joule discreet can be used for wall mounted installations as well.

Accesories



Wall Hanging Swinging Head



Head Module



LJointer



Corner Module



Inward Corner Module



Input Module



- Shows an isometric render & 2D view of a Joule Discreet Power Supply.
- · The power supply must be ordered separately.



Discreet - Tilt Grid 230 - #2239



12W



1041lm




2700K




38°





Photometric Data	
Light source	LED - High Power
Power (W)	12W
Delivered lumens	1041lm
Source lumens	1512lm
Colour temperature (K)	2700K
Luminaire efficacy	86.78/VV
Beam angle	38°
Cutoff angle	NA

Light output ratio	68%
Color rendering index (Ra)	>92
Color rendering index (R9)	>50
Binning MacAdam	<3 SDCM
LED life	L90 B10 Tj75°C
UGR	<19
Operating temperature	-20°C to +50°C
Light distribution	Direct - Symmetric






Technical Data	
Mounting detail	Recessed
Fixing detail	Dual tension spring
Orientation	Adjustable
IP rating	IP20
Glow wire test	850°
Trim material	Aluminium
Heatsink material	Aluminium Extrusion

Product weight	179gms
Safety class	111
Insulation class	III
Voltage	AC230V
Forward voltage	DC24V
Driver	CV - Remote



Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

Matt Black

Custom RAL Color

Reflector Finish

Matt Black

Dimming Options



Non Dimmable Remote Driver

