

Kosmos 24 - #2208



12W




785lm



RGB




10x65°



Photometric Data

Light source	LED - High Power	Light output ratio	72%
Power (W)	12W	Color rendering index (Ra)	NA
Delivered lumens	785lm	Color rendering index (R9)	NA
Source lumens	1080lm	Binning MacAdam	<2 SDCM
Colour temperature (K)	RGB	LED life	L90 B10 Tj75°C
Luminaire efficacy	65.41lm/W	UGR	<19
Beam angle	10x65°	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Grazer



Technical Data

Mounting detail	Surface Mounted	Glow wire test	850°
Fixing detail	Mounting Clamp	Product weight	840gms Per 500MM
Orientation	Adjustable	Safety class	III
IP rating	IP65	Insulation class	III
IK rating	IK05	Driver Input Voltage	AC230V
Trim material	NA	Fixture voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	CV - Remote

Finish Options

Body Finish

-  Matt Grey
-  Custom RAL Color

Length

- 500MM
- 1000MM

Clamp Options



Adj. Clamp

Dimming Options



Remote DMX Decoder

The DMX Decoder requires a 24V CV Driver

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.