

# Kosmos - Flexi Line - #2204



18W/M




1680lm/m



4000K




25x45°



## Photometric Data

|                        |                 |                            |                |
|------------------------|-----------------|----------------------------|----------------|
| Light source           | LED - Mid Power | Light output ratio         | 67%            |
| Power (W)              | 18W/M           | Color rendering index (Ra) | >92            |
| Delivered lumens       | 1680lm/m        | Color rendering index (R9) | >50            |
| Source lumens          | 2502lm/m        | Binning MacAdam            | <2 SDCM        |
| Colour temperature (K) | 4000K           | LED life                   | L90 B10 Tj75°C |
| Luminaire efficacy     | 93.33lm/W       | UGR                        | <19            |
| Beam angle             | 25x45°          | Operating temperature      | -20°C to +50°C |
| Cutoff angle           | NA              | Light distribution         | Grazer         |




## Technical Data


|                 |                          |                      |                   |
|-----------------|--------------------------|----------------------|-------------------|
| Mounting detail | Inground                 | Product weight       | 160gms Per 1000MM |
| Fixing detail   | Mounting Clamp / Profile | Safety class         | III               |
| Orientation     | Top Bendable             | Insulation class     | III               |
| IP rating       | IP67                     | Driver Input Voltage | AC230V            |
| Glow wire test  | 850°                     | Fixture voltage      | DC24V             |
| Trim material   | NA                       | Driver               | CV - Remote       |
| Material        | Silicone                 |                      |                   |

## Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



## Finish Options

### Trim Finish

- ☐ Matt White
- ☐ Matt Grey
- ☒ Custom RAL Color


### Length

5000MM

## Accessories Options



Top Bend  
Radius 300mm



Front  
Cable Entry



Mounting  
Profile



Mounting  
Clamp Fix



Mounting  
Clamp Adj.

## Dimming Options



Constant Voltage Driver  
75w DC24V  
Non Dimmable



Constant Voltage Driver  
75w DC24V  
Triac Dimmable



Constant Voltage Driver  
75w DC24V  
Analog 0-10V / 1-10V Dimmable



Constant Voltage Driver  
75w DC24V  
Dali Dimmable

L'azure constantly strives to improve our products using the latest technological advancements in the industry.  
Due to which the data mentioned in the data sheet is subject to change without prior notice.