

Marcopia Square 4 - #3007



32W





1570lm



Red




5°



Photometric Data

Light source	LED - High Power	Beam angle	5°
Power (W)	32W	Light output ratio	72%
Delivered lumens	1570lm	LED life	L90 B10 Tj75°C
Source lumens	2176lm	UGR	<19
Colour temperature (K)	Red	Operating temperature	-20°C to +50°C
Luminaire efficacy	49.06lm/W	Light distribution	Direct - Symmetric



Technical Data

Mounting detail	Surface Uplichter	Heatsink material	Diecast alm.
Fixing detail	Cowl / Spike / Mounting Bracket	Product weight	1693gms
Orientation	Adjustable	Safety class	III
IP rating	IP65	Insulation class	III
IK rating	IK05	Voltage	DC24V
Glow wire test	850°	Driver	Remote - DC24V

Finish Options

Body Finish

-  Matt Grey
-  Matt Black
-  Custom RAL Color

Filter Options



Honeycomb Filter

Above filters can be added to the fixture and need to be ordered as a separate accessory

Accessories Options



Cowl



Spike

Above accessories can be added to the fixture and need to be ordered as a separate accessory

Dimming Options



Remote DMX Decoder

The DMX Decoder requires a 24V CV Driver