

Recessed M - Brick - #2134



24W





2251lm



3000K





24°



Photometric Data

Light source	LED - High Power	Light output ratio	68%
Power (W)	24W	Color rendering index (Ra)	> 92
Delivered lumens	2251lm	Color rendering index (R9)	> 50
Source lumens	3300lm	Binning MacAdam	< 3 SDCM
Colour temperature (K)	3000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	93.81lm/W	UGR	< 16
Beam angle	24°	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Direct - Symmetric




Technical Data


Mounting detail	Recessed	Product weight	925gms Per 1196MM
Fixing detail	Dual tension spring	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP20	LED current (mA)	Depend on length
Glow wire test	850°	Voltage	AC230V
Trim material	Aluminum	Forward voltage	DC24V
Heatsink material	Aluminum Extrusion	Driver	CV - Remote

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Trim Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

Reflector Finish

- ☒ Specular
- ☐ Pearl Black

Dimming Options



Constant Voltage Driver
75w DC24V
Non Dimmable



Constant Voltage Driver
75w DC24V
Triac Dimmable



Constant Voltage Driver
75w DC24V
Analog 0-10V / 1-10V Dimmable



Constant Voltage Driver
75w DC24V
Dali Dimmable

Note :-

- Although the maximum capacity of the Modules is 10W/133mm for Numinous M, the maximum capacity that the profile in which the modules are placed is 20W/m for Numinous M profile.
- The standard lengths for the Numinous Recessed M fixtures is 1196mm including the endcaps. Each fixture of length 1196mm contains 9 pieces of modules which are placed side by side in the Numinous Recessed M profile. Kindly note - there is no gap in between the modules.

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.