

Peculo Pole Crown - #3120



30W



3025lm



4000K



Diffused



Photometric Data

Light source	LED - High Power
Power (W)	30W
Delivered lumens	3025lm
Source lumens	4260lm
Colour temperature (K)	4000K
Luminaire efficacy	100lm/W
Height	3.0m / 4.0m

Light output ratio	71%
Color rendering index (Ra)	>82
Binning MacAdam	<3 SDCM
LED life	L90 B10 Tj75°C
UGR	<19
Operating temperature	-20°C to +50°C
Light distribution	Direct - Diffused


Technical Data

Mounting detail	Floor - Surface
Fixing detail	Foundation Bolt
Orientation	Fixed
IP rating	IP65
IK rating	IK06
Glow wire test	850°


Body material	Galvanized Steel
Heatsink material	Diecast alm.
Safety class	III
Insulation class	III
Voltage	AC230V
Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- Matt Black
- Matt Grey
- Custom RAL Color

Dimming Options



Constant Current Driver
30w 220-240V
Non Dimmable



Constant Current Driver
30w 220-240V
Triac Dimmable



Constant Current Driver
30w 220-240V
Analog 0-10V / 1-10V Dimmable



Constant Current Driver
30w 220-240V
Dali Dimmable

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.