

Peculo Pole Stem Duo - #3112



2x60W



2x7290lm



4000K



Diffused



Photometric Data

Light source	LED - High Power
Power (W)	2x60W
Delivered lumens	2x7290lm
Source lumens	2x8880lm
Colour temperature (K)	4000K
Luminaire efficacy	121lm/W
Height	4.0m / 6.0m

Light output ratio	82%
Color rendering index (Ra)	>82
Binning MacAdam	<3 SDCM
LED life	L90 B10 Tj75°C
UGR	<19
Operating temperature	-20°C to +50°C
Light distribution	Direct - Diffused


Technical Data

Mounting detail	Floor - Surface
Fixing detail	Foundation Bolt
Orientation	Fixed
IP rating	IP65
IK rating	IK06
Glow wire test	850°


Body material	Galvanized Steel
Heatsink material	Diecast alm.
Safety class	III
Insulation class	III
Voltage	AC230V
Driver	In-built

Photometric Graphs


Hue Bin vs Rf Graph




Color Vector Graphic



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Body Finish

- Matt Black
- Matt Grey
- Custom RAL Color

Dimming Options



Constant Current Driver
60w 220-240V
Non Dimmable



Constant Current Driver
60w 220-240V
Triac Dimmable



Constant Current Driver
60w 220-240V
Analog 0-10V / 1-10V Dimmable



Constant Current Driver
60w 220-240V
Dali Dimmable