

Shuays Fountain F9 - #3060



18W





1701lm



3000K




45°



Note :
This Luminaire can not be operated
out of water for over 15 minutes.

Photometric Data

| | | | |
|------------------------|------------------|----------------------------|--------------------|
| Light source | LED - High Power | Light output ratio | 84% |
| Power (W) | 18W | Color rendering index (Ra) | > 92 |
| Delivered lumens | 1701lm | Color rendering index (R9) | > 50 |
| Source lumens | 2016lm | Binning MacAdam | < 3 SDCM |
| Colour temperature (K) | 3000K | LED life | L90 B10 Tj75°C |
| Luminaire efficacy | 94.54lm/W | UGR | < 19 |
| Beam angle | 45° | Operating temperature | -20°C to +50°C |
| Cutoff angle | NA | Light distribution | Direct - Symmetric |



Technical Data

| | | | |
|-------------------|--------------------------|------------------|----------------|
| Mounting detail | Surface Underwater Light | Glow wire test | 850° |
| Fixing detail | Nozzle Mounted | Product weight | 1096gms |
| Orientation | Fixed | Safety class | III |
| IP rating | IP68 | Insulation class | III |
| IK rating | IK07 | Voltage | DC24V |
| Heatsink material | SS | Driver | Remote - DC24V |
| Ring material | SS | | |

| true Bin | Nt per Bin |
|----------|------------|
| 1 | 96 |
| 2 | 97 |
| 3 | 94 |
| 4 | 93 |
| 5 | 94 |
| 6 | 97 |
| 7 | 97 |
| 8 | 98 |
| 9 | 97 |
| 10 | 95 |
| 11 | 92 |
| 12 | 93 |
| 13 | 93 |
| 14 | 90 |
| 15 | 92 |
| 16 | 91 |

Color Vector Graphic

☐ SS
☒ Custom RAL Color



Constant Voltage Driver
75w DC24V
Dali Dimmable