# Shuays R9 - #3054

27W | 1390lm | Blue | 60°







Note :
This Luminaire can not be operated out of water for over 15 minutes.

## Photometric Data

| | | | |
|---|---|---|---|
| Light source | LED - High Power | Beam angle | 60° |
| Power (W) | 27W | Light output ratio | 90% |
| Delivered lumens | 1390lm | LED life | L90 B10 Tj75°C |
| Source lumens | 1539lm | UGR | <19 |
| Colour temperature (K) | Blue | Operating temperature | -20°C to +50°C |
| Luminaire efficacy | 51.48lm/W | Light distribution | Direct - Symmetric |



## Technical Data

| | | | |
|---|---|---|---|
| Mounting detail | Underwater Light | Glow wire test | 850° |
| Fixing detail | Backbox | Product weight | 1632gms |
| Orientation | Fixed | Safety class | III |
| IP rating | IP68 | Insulation class | III |
| IK rating | IK08 | Voltage | DC24V |
| Heatsink material | SS | Driver | Remote - DC24V |
| Ring material | SS | | |

## Finish Options

Trim Finish

- SS
- Custom RAL Color

## Dimming Options

Remote DMX Decoder

The DMX Decoder requires a 24V CV Driver

L'azure constantly strives to improve our products using the latest technological advancements in the industry.
Due to which the data mentioned in the data sheet is subject to change without prior notice.