

Shuays Surface S3 - #3057



6W




562lm



3000K



30°





Note :
This Luminaire can not be operated
out of water for over 15 minutes.

Photometric Data

Light source	LED - High Power
Power (W)	6W
Delivered lumens	562lm
Source lumens	672lm
Colour temperature (K)	3000K
Luminaire efficacy	93.7lm/W
Beam angle	30°
Cutoff angle	NA

Light output ratio	83%
Color rendering index (Ra)	>95
Color rendering index (R9)	>85
Binning MacAdam	<2 SDCM
LED life	L90 B10 Tj75°C
UGR	<19
Operating temperature	-20°C to +50°C
Light distribution	Direct - Symmetric



Technical Data

Mounting detail	Surface Underwater Light
Fixing detail	Mounting Clamp
Orientation	Adjustable
IP rating	IP68
IK rating	IK07
Heatsink material	SS
Ring material	SS

Glow wire test	850°
Product weight	1324gms
Safety class	III
Insulation class	III
Voltage	DC24V
Driver	Remote - DC24V

Photometric Graphs

Hue Bin vs Rf Graph



Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



Finish Options

Trim Finish

- ☐ SS
- ☒ Custom RAL Color

Dimming Options



Constant Voltage Driver
75w DC24V
Non Dimmable



Constant Voltage Driver
75w DC24V
Triac Dimmable



Constant Voltage Driver
75w DC24V
Analog 0-10V / 1-10V Dimmable



Constant Voltage Driver
75w DC24V
Dali Dimmable