

Willow Recessed R - #3062



3W





239lm



3000K




Asymmetric



Photometric Data

Light source	LED - High Power	Light output ratio	71%
Power (W)	3W	Color rendering index (Ra)	>92
Delivered lumens	239lm	Color rendering index (R9)	>50
Source lumens	336lm	Binning MacAdam	<3 SDCM
Colour temperature (K)	3000K	LED life	L90 B10 Tj75°C
Luminaire efficacy	79.67lm/W	UGR	<19
Beam angle	Asymmetric	Operating temperature	-20°C to +50°C
Cutoff angle	NA	Light distribution	Asymmetric



Technical Data

Mounting detail	Recessed	Product weight	157gms
Fixing detail	Wall Mounted	Safety class	III
Orientation	Fixed	Insulation class	III
IP rating	IP54	Voltage	AC230V / DC24V
Glow wire test	850°	Driver	In-built - AC230V
Trim material	Diecast alm.		Remote - DC24V
Heatsink material	Diecast alm.		

True Bin	N of test cases
1	96
2	97
3	94
4	93
5	97
6	97
7	98
8	99
9	97
10	95
11	93
12	93
13	93
14	90
15	92
16	91

A color vector graphic showing a smooth gradient from blue on the left to red on the right, with green at the top and purple at the bottom. A large white circle is centered on the gradient. The text "Color Vector Graphic" is visible in the top right corner.

☐ Matt White
☐ Matt Black
☐ Custom RAL Color

Dimming Options



Constant Voltage Driver
36w DC24V
Non Dimmable



Constant Voltage Driver
36w DC24V
Triac Dimmable



Constant Voltage Driver
36w DC24V
Analog 0-10V / 1-10V Dimmable



Constant Voltage Driver
36w DC24V
Dali Dimmable