

# iSkew Flat Mini Fix - #1318



5W






381lm



2700K




24°



## Photometric Data

|                        |             |                            |                    |
|------------------------|-------------|----------------------------|--------------------|
| Light source           | LED - Array | Light output ratio         | 83%                |
| Power (W)              | 5W          | Color rendering index (Ra) | >95                |
| Delivered lumens       | 381lm       | Color rendering index (R9) | >85                |
| Source lumens          | 455lm       | Binning MacAdam            | <2 SDCM            |
| Colour temperature (K) | 2700K       | LED life                   | L90 B10 Tj75°C     |
| Luminaire efficacy     | 76.31lm/W   | UGR                        | <19                |
| Beam angle             | 24°         | Operating temperature      | -20°C to +50°C     |
| Cutoff angle           | NA          | Light distribution         | Direct - Symmetric |



## Technical Data

|                   |                           |                  |             |
|-------------------|---------------------------|------------------|-------------|
| Mounting detail   | Ceiling - Recessed 1-25mm | Product weight   | 89gms       |
| Fixing detail     | Dual tension spring       | Safety class     | III         |
| Orientation       | Fixed                     | Insulation class | III         |
| IP rating         | IP20                      | LED current (mA) | 120mA       |
| Glow wire test    | 850°                      | Voltage          | AC230V      |
| Trim material     | Diecast alm.              | Forward voltage  | DC36V       |
| Heatsink material | Diecast alm.              | Driver           | CC - Remote |

## Photometric Graphs

Hue Bin vs Rf Graph



Color Vector Graph



Spectrum vs Wavelength Graph



CIE Chromaticity Graph



## Finish Options

### Trim Finish

- ☐ Matt White
- ☒ Matt Black
- ☐ Custom RAL Color

### Interior Finish

- ☐ Matt White

## Dimming Options



Constant Current Driver  
5w 120mA 220-240V  
Non Dimmable



Constant Current Driver  
5w 120mA 220-240V  
Triac Dimmable



Constant Current Driver  
5w 120mA 220-240V  
Analog 0-10V / 1-10V Dimmable



Constant Current Driver  
5w 120mA 220-240V  
Dali Dimmable



Constant Current Driver  
5w 120mA 220-240V  
Dali Tunable



Constant Current Driver  
5w 120mA 220-240V  
RF Tunable (operated with RF remote)

L'azure constantly strives to improve our products using the latest technological advancements in the industry.  
Due to which the data mentioned in the data sheet is subject to change without prior notice.